



Pitch Range In mm	Nominal Dimension Range In mm						-1/2
	Over 6	Over 10	Over 10	Over 30	Over 60	Over 100	
TO 6	TO 10	TO 24	TO 30	TO 60	TO 100	TO 150	≤
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	
							±2

ITEM	NAME OF PART	MATERIAL	NOTES
7	Pin header 2	Copper alloy	Sn Plated
6	Pin header 1	Copper alloy	Sn Plated
5	Nut	Steel	Zn Plated
4	Screw	Steel	Ni Plated
3	Cover 2	PC	UL94V-0
2	Cover 1	PC	UL94V-0
1	Housing 1	PBT	UL94V-0

MATERIAL:	/
MAT NO.:	/
STATUS:	/
APPD:	
CHKD:	

UL 标准/UL Standard: B C D
 额定电压/电流/Rated Voltage(V)/Current(A) 300/8 / 300/10
 螺丝扭矩/Torque Tightening(N·m/Lb·in) M3, 0.5/4.43
 导线范围(导线)/Wire Range(Flexible)(AWG) 14~22
 间距/Pitch(mm)/线数范围/Poles 7.62/N=10~48P(偶数)
 使用温度范围/Operating temperature(°C) -40~+120
 符合RoHS环保要求/Conform to RoHS Yes

NAME:	DG24-4-XXP-11-00A(H)	
DRAWING NO.:	DG24B-2-C01	REV T0
TYPE:	CUSTOMER DRAWING	SCALE: 1:1 SHEET 1/2

REV	ECN	DESCRIPTION	DRAFT	DATE

1	2	3	4	5	6
---	---	---	---	---	---

D

C

B

A

D

C

B

A

DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD
 宁波高松电子有限公司

DG24-4-XXP-11-00A(H)