



公差/General	公差/General	公差/General	公差/General	公差/General	公差/General	公差/General	公差/General	公差/General	公差/General	公差/General	公差/General	公差/General	公差/General	公差/General	公差/General	公差/General	公差/General	公差/General
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	>630	>800	>1000	>1250	>1600
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±1.05	±1.15	±1.60	±2.20	±2.50	±3.15	±4.00	±5.00	±6.30	±8.00	±10.00

ITEM	NAME OF PART	MATERIAL	NOTES
4	Cover	PC	UL94V-2
3	Pin header	Copper alloy	M4/Sn plated
2	Screw	Steel	M4/Ni plated
1	Housing	PA66	UL94V-0

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	600/40	600/40	600/5
IEC 标准/IEC Standard:	过压类别/Overvoltage Category/污染等级/ Pollution Degree		
额定电压/电流/Rated Voltage(V)/Current(A)	III/3	III/2	II/2
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	1000/41	1000/41	1000/41
额定脉冲电流(KV)/Rate Impulse Current(KV)	8	8	8
额定扭矩/Torque Tightening(N·m/Lb·in)	M4, 1.16/10.5		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.75~6/18~10		
可抽/Pitch(mm)/线数范围/Poles	13/N=02~18P		
剥线长度/Stripping length(mm)	9~10		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

MATERIAL: / SURFACE: /

MAT NO.: /

STATUS: /

APPD: /

CHKD: /

DRFT: XieXD 2020.06.15

NAME: **DEGSON** 宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD

DRAWING NO.: DG78C-C01

TYPE: CUSTOMER DRAWING

REV	ECN	DESCRIPTION	DRFT	DATE