



未注公差/General tolerances (mm)													0.1/10	
0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500		>500
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2'

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless authorized in writing by Degson. All rights reserved for patent. 未经授权复制或传播本文件内容，或在本文件中进行任何修改、复制或再行发布，均属于侵权行为。本公司保留对本文件的所有权利。

ITEM	NAME OF PART	MATERIAL	NOTES
3	Housing	PA66	UL94V-0
2	Nut	Steel	Zn Plated
1	Pin header	Copper alloy	Sn Plated
额定电流/Rated Current(A)		40A	
螺丝扭矩/Torque Tightening(N·m/Lb.in)		M4, 1.8/15.79	
符合RoHS环保要求/Conform to RoHS		Yes	

		MATERIAL:	SURFACE/COLOR:			
APPD: 蓝贵凡 2023.05.10		MAT NO./REV: 10900000246-1 / 00		MAT STATUS: 批量		
CHKD: 曹利彬 2023.05.04		NAME: K31-13A(H)				
DRFT: 姜民洁 2023.05.04		DRAWING NO.	TYPE	DRAWING STATUS	SCALE	SHEET
A4		200191789	CUSTOMER DRAWING	已发布	2:1	1/1

REV	ECN	DESCRIPTION	DRFT	DATE
00			姜民洁	2023.05.04