

<b>Technical Information</b>	
Product Description	Serial port module, 1 channel, supporting RS232/RS485/RS422
Number of channels	1
interface	RS232/RS485/RS422
protocol	Modbus RTU/ASCII master and slave modes; Free Agreement Mode
Baud	1200bps—500000bps
Data bits	7bit/8bit
Check digit	None/Even/Odd/Space/Mark
Stop bit	1bit/1.5bit/2bit
Maximum data frame length	128byte
<b>Wiring parameters</b>	
Connection technology: input end	PUSH-IN type wiring port
line type	Input
Crimping area of wire	0.14~1.5mm <sup>2</sup> /26~16AWG
Strip length	8~10mm
Installation method	DIN-35 type guide rail
<b>Material parameters</b>	
Colour	Black
Housing material	PC plastic, PA66
Consistency flag	CE
<b>Environmental requirements</b>	
Permissible ambient temperature (during operation)	-25~60℃
Permissible ambient temperature(storage)	-40~85℃
Protection type	IP20
Pollution leve	2. Comply with IEC 61131-2 standard
Working altitude	Without temperature influence:0~2000m
Relative humidity (non condensing)	5~95%RH
Anti vibration	4g, Complies with IEC 60068-2-6 standard
Impact resistance	15g, Complies with IEC 60068-2-27 standard
EMC - Immunity	Complies with EN 61000-6-2 standard
EMC-Radiated Interference	Complies with EN 61000-6-3 standard
Corrosion resistance	Complies with IEC 60068-2-42 and IEC 60068-2-43 standards
Permissible H2S pollutant concentration at 75% relative humidity	10ppm
Permissible SO2 pollutant concentration at 75% relative humidity	25ppm
Firmware upgrade	support